

## Accessories for OPTIMAT® and OPTIMAT® dispensing pumps


### Intake tube, length 1 m

Volume	Art.-Nr. PTFE	Art.-Nr. Silicone
1 ml	101.132-01	-
2 ml	101.132-02	-
10 ml	101.132-02	-
30 ml	101.132-04	101.132-06
50 ml	101.132-04	101.132-06
100 ml	101.132-04	101.132-06
200 ml	101.132-04	101.132-06
300 ml	101.132-04	101.132-06



### Discharge tube set made of PTFE

Volume	Art.-Nr. 0.75 m	Art.-Nr. 1.50 m
1 ml	101.134-02	101.134-03
2 ml	101.134-02	101.134-03
10 ml	101.134-02	101.134-03
30 ml	101.134-04	101.134-05
50 ml	101.134-04	101.134-05
100 ml	101.134-04	101.134-05
200 ml	101.134-04	101.134-05
300 ml	101.134-04	101.134-05



### 101.136-20 Foot Pedal for START/STOP function



**155.000-40 Serial Cable** (without picture)

Packing unit: 1

# Poulten & Graf

SUPERIOR LABORATORY PRODUCTS

## FORTUNA® OPTIMAT® 3



### New Features

- Large touch screen display for better reading precision
- New software for better handling
- Language selection possible



**Poulten & Graf Ltd**  
Peak Works, 1 Alfreds Way  
Barking, Essex,  
IG 11 OAS, UK  
Tel.: +44 (0)20 8594 4256  
Fax: +44 (0)20 8594 8419  
www.poulten-graf.co.uk  
VOLAC@poulten-graf.com

**Poulten & Graf GmbH**  
Karl-Carstens-Str. 10,  
97877 Wertheim, Germany  
Tel.: +49 9342 9229-0  
Fax: +49 9342 9229-80  
www.poulten-graf.de  
sales@poulten-graf.com  
www.shop.poulten-graf.de

**FORTUNA®**





# FORTUNA® OPTIMAT® 3

## Automatic programmable Dispensing Station

**Art.-No. 150.000-3**  
(Pump and tubes are  
not included / please  
order separately)

### Technical Features


- Precision drive
- Colour touch screen
- Suitable for continuous operation
- 8 pump sizes available

### Benefits

- designed to give years of continuous day-in day-out service
- high level of precision
- dispenses even difficult and aggressive liquids
- extremely robust
- dispensing without corrosion or contamination (no metal components in the pump)

### Typical Applications

- calibration of volumetric apparatus
- extremely accurate dispensing of strong acids, alkalis, high value chemicals in the pharmaceutical and cosmetic industries



## FORTUNA® OPTIMAT® dispensing pump

for dispensing strong fuming acids and very abrasive liquids,  
single pack (intake and discharge tube sets are not included)

Volume	Grad.	A* <sub>≤ ±</sub>	CV* <sub>≤ ±</sub>	max.V	Art.-No.
0 - 1 ml	0.05 ml	± 0.6 %	± 0.2 %	0,55 ml/s	101.126-20
0 - 2 ml	0.1 ml	± 0.6 %	± 0.2 %	1,90 ml/s	101.126-27
0 - 10 ml	0.2 ml	± 0.6 %	± 0.2 %	3,35 ml/s	101.126-38
0 - 30 ml	0.5 ml	± 0.6 %	± 0.2 %	9,60 ml/s	101.126-44
0 - 50 ml	1.0 ml	± 0.6 %	± 0.2 %	15,20 ml/s	101.126-48
0-100 ml	2.0 ml	± 0.6 %	± 0.2 %	24,30 ml/s	101.126-51
0-200 ml <sup>(1)</sup>	5.0 ml	± 0.6 %	± 0.2 %	31,30 ml/s	101.126-53
0-300 ml <sup>(1)</sup>	5.0 ml	± 0.6 %	± 0.2 %	31,80 ml/s	101.126-56

Packing unit: 1

\* A=Accuracy, CV=Coefficient of variation

<sup>(1)</sup> additional to ISO 8655